

Protects New Floors - Renews Old Floors

For use on both new and old floors. Asphalt tile, Vinyl Asbestos, Linoleum, Vinyl rubber, Cork, Concrete, Terroazzo, Magnesite, Travertine.

This remarkable product seals the floor itself against water, stains and soiling. It provides a salt and detergent-resistant base coat or can be used as both base coat and top coat.

DIRECTIONS

PREPARATION OF FLOOR:

For best results, floor must be thoroughly cleaned and rinsed. All previous floor finish or wax should be completely removed by use of heavy duty wax cleaner-wax stripper. Cleaner-stripper should be completely rinsed, then allow floor to dry.

APPLICATION OF UNDERCOATER-SEALER:

Apply Acrylic Undercoater-Sealer to clean, dry floor using rayon mop or lambs wool applicator. Spread product evenly over entire floor area. Avoid excessive agitation of product and do not allow material to dry in puddles. After product is dry, inspect for uniform coverage. A very porous floor may require a second coat.

KEEP OUT OF REACH OF CHILDREN

Use only in accordance with directions.

Lewis County Chemical

1970 A South Market Blvd., Chehalis, WA 98532
(360) 748-0336 ~ 1-800-872-5421

Contents 1 Gallon

Lewis County Chemical
Janitorial & Paper
PRODUCTS

1st
Acrylic
Undercoater-Sealer

Eccothane X-22

High Solids Extreme Performance Floor Coating

An extreme performance floor coating that combines deep gloss, high durability and ease-of-use into one product. High molecular weight acrylic polymers and dense cross-linking produce a beautiful, long lasting shine that resists black marking and scuffing. This finish is ideal for limited maintenance settings such as classrooms, patient rooms and offices. It also responds to occasional burnishing - making it suitable for retail establishments, hallways and other frequently maintained areas.

DIRECTIONS

APPLICATION:

1. Strip floors to remove old waxes, sealers and finishes.
2. Rinse thoroughly and let dry.
3. With a clean equipment apply thin, even coats of finish..
4. Under normal conditions, allow to dry for 30 minutes between coats.
5. For best results, apply a maximum of 4 coats in 24 hours.

NOTE: For stripping and maintaining asbestos containing tile, follow OSHA guidelines or EPA guidelines.

COVERAGE: One gallon covers up to 3,000 square feet.

MAINTENANCE:

1. **DAILY:** Sweep or dust mop as necessary to remove gritty soil.
2. **DIRTY FLOORS:** Clean with 2-4 oz. of neutral floor cleaner per gallon of water. Rinse and let dry.
3. **TRAFFIC AREA:** Clean with 2-4 oz. of neutral floor cleaner

per gallon of water. Rinse and let dry. Apply additional thin coats of floor finish to traffic lanes as needed.

4. **BUFFING:** If desired, periodic burnishing with hair pads will enhance appearance.

5. **PERIODIC COMPLETE MAINTENANCE:** Ordinarily, stripping is not required more than (1) or (2) times per year. Use up to 32 oz. of our stripper per gallon of warm water.

CAUTION:

May irritate eyes, skin and gastrointestinal tract. Use in poorly ventilated area may cause respiratory irritation. Avoid eye and skin contact. Use with adequate ventilation

FIRST AID:

EYE & SKIN CONTACT: Flush with water (eyes 15 minutes).
INGESTION: If swallowed give 2-3 large glasses of water. Seek medical attention in all cases if symptoms persist.

Lewis County Chemical

1970 A South Market Blvd., Chehalis, WA 98532
(360) 748-0336 ~ 1-800-872-5421

Contents 1 Gallon

Eccothane
X-22

Mop & Buff Floor Restorer

Cleans and Restores Floors to Full Beauty.

Use weekly to quickly and easily clean and restore floors to full beauty. This floor restorer is a concentrate made to be mixed with water and mopped on floors like a cleaner. It dries dull and then is buffed to full brilliance with any speed floor machine. Performs best when used with ultra high speed machines and ultra high speed pads. Combined with daily floor cleaning, the weekly use of this restorer permits everyone to have beautiful floors. Heavy traffic floors may require more frequent restorer treatment or re-coating with floor finish.

How to use:

1. Dry mop floors to remove surface grit. For best results, auto scrub soiled floors with a neutral cleaner and red pads.
2. This restorer can be used with all speed floor machines ... - for 1500-2000 rpm ultra high speed machine burnishing, mix 1 qt. of Restorer with 1 gal. water. For 1000 rpm high speed machine burnishing, mix 1 qt. of Restorer with 3 gals. of water.
3. Damp mop the floor with the restorer-water solution.
4. Burnishing/buff when dry.

CAUTION

EYE CONTACT: Direct eye contact with finish may result in irritation.
INGESTION: Irritant to gastrointestinal tract.

FIRST AID

EYE CONTACT: IMMEDIATELY WASH EYES WITH LARGE AMOUNT OF WATER FOR AT LEAST 15 MINUTES.

SWALLOWED: Give 2 glasses of water. Call a physician.

SPILLS & LEAKS: Dike and contain spill. Collect on inert material (sand, earth, etc.) Take inert material to chemical landfill in accordance with all federal, state and local regulations. Do not allow runoff into public waterways.

KEEP OUT OF REACH OF CHILDREN.

For Commercial, Industrial and Institutional Use Only.

Lewis County Chemical

1970 A South Market Blvd., Chehalis, WA 98532
(360) 748-0336 ~ 1-800-872-5421

Contents 1 Gallon

Lewis County Chemical
Janitorial & Paper
PRODUCTS

Restore - It
Mop & Buff
Floor Restorer

NO RINSE WAX STRIPPER

Removes Floor Waxes, Finishes or Floor Sealers

Use to remove: Floor Waxes-carnauba; Floor Finishes-acrylic, styrene, polymers, oligimers, metal crosslinked; Floor Sealers-acrylic, water based urethane.

DIRECTIONS

1. Dilute with hot water as follows: **Normal:** 1 part to 5 parts water. **Heavy Build-up:** 1 part to 1 part water. **Automatic Scrubber:** 1 part to 10 parts water.

2. Apply liberally with mop to floor. Be sure to leave surface VERY wet!

3. Allow to remain 3 to 4 minutes and remop. This provides slight agitation necessary for 100% removal of old floor finish. Allow another 3 minutes before vacuuming.

4. Pick up solution using a wet vac. If any finish remains (such as around baseboards) use a bowl swab and DILUTED stripper to touch up.

5. Allow floor to dry. No rinsing is necessary if surface appears free of dust after drying. All stripper solution will evaporate.

6. Recoat.

NOTE: In order to determine use dilution, pre-test on a small area. Strip only a manageable area at one time. Although pick-up using a wet vac is advised, the solution may be mopped off the floor.

CAUTION:

1. This product does not contain the highly caustic alkali associated with most strippers. However, because of its unusual penetrating and dissolving ability, it must be used only as directed. **DO NOT USE UN-DILUTED.**

2. **Wet floor may become extremely slippery. Be sure to keep pedestrian traffic away from floor until thoroughly dry.**

WARNING: Prolonged exposure to high concentrations of vapor may be harmful to eyes, skin and respiratory tract. Work area should have adequate ventilation. May be harmful if swallowed.

FIRST AID: In case of contact, flush eyes or skin with plenty of water. For eyes, get medical attention immediately. If swallowed, drink milk or large quantities of water. Get medical attention. **SPILLS & LEAKS:** Collect and reuse, if possible. Flush to sewer with large quantity of water, if permitted by Federal, State and Local Regulations.

KEEP OUT OF REACH OF CHILDREN. Use only in accordance with directions. Only for Sale to, Use, and Storage by Servicepersons.

Lewis County Chemical

1970 A South Market Blvd., Chehalis, WA 98532

(360) 748-0336 - 1-800-872-5421

Contents

1 Gal.

HARD N' FAST ACRYLIC FLOOR FINISH

Fast Drying - Brilliant Gloss

This hard, fast drying and fast curing finish provides complete floor protection instantly. A scrubable time saving finish for all floors. Very hard, heel mark and scuff resistant dries to a beautiful high gloss. Designed for heavy traffic. Spray buffable.

DIRECTIONS: Floor should be properly stripped of all old wax, etc., prior to applying Floor Finish.

MAINTENANCE:

1. Daily: Sweep as necessary to remove gritty soil.

2. Dirty Floors: Clean with 2 to 4 ozs. Floor Cleaner per gallon of water. Rinse and let dry.

3. Traffic Area: Clean with 2 to 4 ozs. Floor Cleaner per gallon of water. Rinse and let dry. Then apply a thin coat of Floor Finish to traffic area.

4. Periodic Complete Maintenance: Stripping not required ordinarily more than one or two times per year. Use 10 to 16 ounces of Stripper per gallon of hot water. A stripping pad is recommended for fastest stripping. Let dry thoroughly and recoat.

PREPARATION

1. Use Wax Stripper to remove old wax, finish, resin and soil.

2. A scrubbing machine is most efficient. (Stripping pads may be used to expedite cleaning).

3. Rinse thoroughly and let dry. Keep away from children.

APPLICATION
1. Use only clean equipment (applicator, mops and pails), in applying the finish.

2. Apply thin, even coat. Do not rub! Another thin coat is recommended for added gloss and protection. One gallon covers 2,500 sq. ft.

3. Allow 15-20 minutes for drying before applying a second coat.

CAUTION: EYE CONTACT: Direct eye contact with finish may result in irritation. **INGESTION:** Irritant to gastrointestinal tract.

FIRST AID: EYE & SKIN CONTACT: Immediately wash eyes with large amount of water for at least 15 minutes.

SWALLOWED: Give 2 glasses of water. **DO NOT** induce vomiting. Call a physician.

SPILLS & LEAKS: Stop spill at source. Dike to prevent spreading and absorb on inert material. Take inert material to chemical landfill. **DO NOT** allow runoff into public waterways.

Lewis County Chemical

1970 A South Market Blvd., Chehalis, WA 98532

(360) 748-0336 ~ 1-800-872-5421

Contents 1 Gallon

WATER SOLUBLE CONCENTRATED ALL PURPOSE DEGREASER

Amazing non-butyl cleaner degreaser that removes animal, vegetable and petroleum oils and greases better than any butyl base product. This total detergent system emulsifies and holds oily soil in suspension for easy rinsing or wiping. Controlled foam for freer rinsing. Odor counteractant for professional deodorizing, non-flaming, non-flammable.

For removing grease, oil, soot, carbon, printer's ink, crayon, lipstick, food spills, wax, floor finish, rubber burns, algae and mildew stains, etc. For use in food processing plants, restaurants, dairies, institutions, industrial and agricultural users.

DIRECTIONS

Heavy grease & oil removal:dilute 1 part cleaner with 2-5 parts of warm water.

General Cleaning and degreasing:dilute 1 part cleaner with 8-10 parts water.

Steam Cleaning:dilute 1 part cleaner with 8-16 parts water.

High Pressure Washing:dilute 1 part cleaner with 40-80 parts water.

Automatic Scrubbing:dilute 1 part cleaner with 40-80 parts water.

Wet Mopping and Sponging:dilute 1 part cleaner with 40-80 parts water.

Use on all surfaces not harmed by water. Rinse thoroughly or wipe clean after use. Because it contains no perfume or butyl cellosolve it imparts no odors in food processing plants. Food equipment and surfaces subject to contact with food should be rinsed thoroughly with potable water after cleaning procedure.

DANGER: Corrosive Liquid. Contact causes burns of eyes and skin. Vapor irritating to eyes, skin and nasal mucous membranes. Harmful if swallowed.

FIRST AID: Inhalation: Move subject to fresh air and give artificial respiration. Call a Physician. **SWALLOWED:** Give 2 glasses of water to drink. **DO NOT INDUCE VOMITING.** Call a physician. **SPILLS & LEAKS:** Dike and contain spill with inert material (sand, earth). Collect into closed container for disposal according to local, state and federal regulations. **EYE AND SKIN CONTACT:** Immediately get under a safety shower. Flush eyes with water while removing contaminated clothes and flooding exposed skin areas with water. Call a Physician.

KEEP OUT OF REACH OF CHILDREN. Use only in accordance with directions.

Lewis County Chemical

223 N.W. Chehalis Ave., Chehalis, WA 98532

(360) 748-0336 - 1-800-872-5421



Lewis
County
Chemical

SOFT SUDS

LOTIONIZED
HAND DISHWASH



LEWIS COUNTY CHEMICAL
JANITORIAL AND PAPER PRODUCTS

Hard n' Fast
Acrylic
Floor Finish



Lewis
County
Chemical

FAST 'N EASY
WATER SOLUBLE
CONCENTRATED

ALL PURPOSE DEGREASER

ALL PURPOSE CONCENTRATE CLEANER

A Safe, Concentrated, Versatile, Chemically Balanced All Purpose Liquid Cleaner
Dilute to the proper consistency for best results.

DIRECTIONS:

FLOORS: Can be used on linoleum, rubber, asphalt, synthetic, vinyl, marble, terrazzo, hard tile & wood floors.

GENERAL CLEANING - 1 part concentrate to 25 parts water.

EXTREME SOIL - 1 part concentrate to 10 parts water.

WAX STRIPPING - 1 part concentrate to 3 - 6 parts hot water.

AMMONIA - 4 - 6 oz. per gal. may be added for faster results on heavy build-up.

SCRUBBING MACHINES - Weaker solutions than recommended above may be used, depending on soil conditions.

DAMP MOPPING - 1 part concentrate to 40 parts water.

ALSO EXCELLENT FOR:

Automobiles - For hand cleaning - dilute 1 to 50 with water; rinse thoroughly.

ALUMINUM - **STAINLESS STEEL** - Dilute 1 to 25 with warm water. Apply with clean cloth, agitating lightly. Wipe with damp cloth; then dry with clean dry cloth.

FURNITURE AND WOODWORK - Dilute 1 to 25 with water. Wipe with damp cloth then dry with clean dry cloth.

GLASS - dilute 1 to 50 with water.

GYM FLOORS - Dilute 1 to 6 parts hot water; let stand and scrub if necessary. For scuff or stains on baseboards, apply steel wool with solution and rub lightly.

LEATHER - **PLASTIC UPHOLSTERY** - Dilute 1 to 20 with water.

Wipe with clean damp cloth or sponge dry with clean dry cloth.

WARNING - Contains alkaline cleaning agents. May irritate eyes and sensitive skin. Use with adequate ventilation.

FIRST AID - In case of contact, flush eyes or skin with plenty of water. For eyes, get medical attention immediately. If swallowed, drink milk or large quantities of water. Get medical attention.

SPILLS OR LEAKS - Collect and reuse, or flush to sewer if allowed by local regulations. Rinse area with water.

KEEP OUT OF REACH OF CHILDREN.

Use only in accordance with directions.

Lewis County Chemical

1970 A South Market Blvd., Chehalis, WA 98532
(360) 748-0336 ~ 1-800-872-5421

Contents 1 Gallon

Lewis County Chemical
Janitorial & Paper
PRODUCTS

LCC
Concentrate
ALL PURPOSE CLEANER

CAR & TRUCK WASH & POLISH

For Washing: Cars – Trucks – Trailers – Equipment

Designed for all types of carwashing. Hand, power spray, pressure and automatic systems all work better with this super carwash. Cleans surfaces so they shine like new. Free rinsing. Water and soil disappear. No wiping needed. Excellent results in all types of water. It's biodegradable. It's concentrated – a little goes a long way. Easy on hands. Easy on cars.

DIRECTIONS

GENERAL CARWASHING: Use 1/2 oz. to 1 oz. per gallon of water. Wet down car before washing. Wash top of car and rinse. Wash one side at a time. Wash and rinse wheels and bumpers last. Remove any water beads remaining on surface. After rinsing allow car to dry in shade.

CAUTION

EYE CONTACT: Direct eye contact may cause irritation, redness, burning. **INGESTION:** May cause nausea and diarrhea.

FIRST AID

EYE CONTACT: Immediately flush eyes with large amounts of water (15 minutes), occasionally holding eyelids open. **INGESTION:** Give 2 glasses of water.

SPILLS OR LEAKS

Stop spill at source, collect and reuse if possible. Flush area with water. Flush to sewer where allowed by state, local and federal regulations.

KEEP OUT OF REACH OF CHILDREN. Use only in accordance with directions.

Lewis County Chemical

223 N.W. Chehalis Ave., Chehalis, WA 98532
(360) 748-0336 – 1-800-872-5421

BLUE
RIBBON
PRODUCTS

Lewis
County
Chemical

Clean & Shine

CAR & TRUCK
WASH & POLISH

NEUTRAL ALL PURPOSE CLEANER

Neutral pH – Mop On / Mop Off

An excellent product for damp mopping. Contains no harsh alkalies or acids to leave an after film. This product was specially designed as an effective neutral low foaming cleaner, free from acids and alkalies, non butyl, neutral pH, non corrosive, non toxic. It will not cause corrosion of soft metals such as aluminum, magnesium and zinc.

It dilutes clearly without a precipitate in hard water, either hot or cold. Will not clog orifices in nozzles of automatic scrubbers and pressure sprayers.

DIRECTIONS

General Cleaning and Degreasing - dilute 1 part cleaner with 8-10 parts water.

Wet Mopping and Sponging - dilute 1 part cleaner with 40-80 parts water.

Heavy Grease and Oil Removal - dilute 1 part cleaner with 2-5 parts warm water.

Steam Cleaner - dilute 1 part cleaner with 8-16 parts water.

High Pressure Washing - dilute 1 part cleaner with 40-80 parts water.

Automatic Scrubbing - dilute 1 part cleaner with 40-80 parts water.

CAUTION: Do not get concentrate in eyes. Avoid contamination of food. For extensive use, wear rubber gloves. Harmful if swallowed.

FIRST AID: In case of contact, flush eyes or skin with plenty of water. For eyes, get medical attention immediately. If swallowed, drink milk or large quantities of water. Get medical attention.

SPILLS OR LEAKS: Collect and reuse, or flush to sewer if allowed by local regulations. Rinse area with water. Only for Sale to, Use and Storage by Servicepersons.

KEEP OUT OF REACH OF CHILDREN.

Use only in accordance with directions.

507

BLUE
RIBBON
PRODUCTS

Lewis
County
Chemical

Enviro-Clean

NEUTRAL
ALL PURPOSE CLEANER

Lewis County Chemical

223 N.W. Chehalis Ave., Chehalis, WA 98532
(360) 748-0336 – 1-800-872-5421

HEAVY DUTY CLEANER - DEGREASER - STRIPPER

Effectively strips wax, grease, synthetic finishes, soap, oil, dirt, sludge and other films. Chemically penetrates, reacts and suspends greasy soil and wax in solution for easy rinsing. Spray, Brush or Mop On and RINSE THOROUGHLY. Higher concentrations may be used for extreme soil, less for light soil.

GENERAL DIRECTIONS: General Cleaning - 1 to 40 water, Light - 1 to 60 water, Heavy - 1 to 20 water.

Acoustical Tile.....	1 to 40 water	Machine Sumps.....	1 to 10 water
Air Conditioning (ducts, grills).....	1 to 20 water	Metal Surfaces (greasy).....	1 to 10 water
Air Filters.....	1 to 4 water	Plastics.....	1 to 40 water
Concrete Floors.....	1 to 20 water	Printing Plants (presses, type).....	1 to 10 water
Conveyers.....	1 to 10 water	Refrigerators.....	1 to 30 water
Damp Mopping.....	1 to 60 water	Scrubbing Machines.....	1 to 20 water
Engines, Motors, Machinery.....	1 to 2 water	Shower Stalls.....	1 to 10 water
Exhausts, Flues, Firebrick.....	1 to 2 water	Stainless Steel *Aluminum.....	1 to 20 water
Kitchens (walls, ceiling, tile).....	1 to 20 water	Swimming Pools.....	1 to 10 water
Kitchens, (ovens).....	1 to 4 water	Terrazzo - Tile - Marble.....	1 to 30 water
Washroom Fixtures.....	1 to 4 water	Wax Stripping (regular).....	1 to 10 water
Lighting Fixtures.....	1 to 40 water	Wax Stripping (extra heavy).....	1 to 5 water
Linoleum - Asphalt - Rubber Tile.....	1 to 40 water	White Sidewall Tires.....	1 to 4 water

DANGER: Corrosive Liquid. Contact causes burns on eyes and skin. Vapor irritating to eyes, skin and nasal mucous membranes. Harmful if swallowed. **First Aid:** Inhalation: Move subject to fresh air and give artificial respiration. Call a physician. Eye and Skin Contact: Immediately get under a safety shower. Flush eyes with water while removing contaminated clothes and flooding exposed skin areas with water. Call a physician. Ingestion: Give 2 glasses of water to drink. **DO NOT INDUCE VOMITING.** Call a physician. Spills and Leaks: Side and contain spill with inert material (sand, earth). Collect into closed container for disposal according to local, state and federal regulations. **KEEP OUT OF REACH OF CHILDREN.**

Lewis County Chemical

1970 A South Market Blvd., Chehalis, WA 98532

(360) 748-0336 ~ 1-800-872-5421

Contents 1 Gallon



LEWIS COUNTY CHEMICAL
JANITORIAL AND PAPER PRODUCTS



Knock Out
Heavy Duty Cleaner
Degreaser - Stripper

NO RINSE WAX STRIPPER

Removes Floor Waxes, Finishes or Floor Sealers

Use to remove: Floor Waxes-carnauba: Floor Finishes-acrylic, styrene, polymers, oligimers, metal crosslinked; Floor Sealers-acrylic, water based urethane.

DIRECTIONS

1. Dilute with hot water as follows:

Normal: 1 part to 5 parts water.

Heavy Build-up: 1 part to 1 part water.

Automatic Scrubber: 1 part to 10 parts water.

2. Apply liberally with mop to floor. Be sure to leave surface VERY wet!
3. Allow to remain 3 to 4 minutes and re mop. This provides slight agitation necessary for 100% removal of old floor finish. Allow another 3 minutes before vacuuming.
4. Pick up solution using a wet vac. If any finish remains (such as around baseboards) use a bowl swab and DILUTED stripper to touch up.
5. Allow floor to dry. No rinsing is necessary if surface appears free of dust after drying. All stripper solution will evaporate.
6. Recoat.

NOTE: In order to determine use dilution. Pre-test on a small area. Strip only a manageable area at one time. Although pick-up using a wet vac is advised, the solution may be mopped off the floor.

KEEP OUT OF REACH OF CHILDREN. Use only in accordance with directions. Only for Sale to, Use and Storage by Servicepersons.

DOT Hazard Class: Corrosive Material

Proper Shipping Name: Caustic Alkali Liquid, N.O.S. (Monoethanolamine) 8, UN 1719, PGIII

Lewis County Chemical

1970 A South Market Blvd., Chehalis, WA 98532

(360) 748-0336 ~ 1-800-872-5421

Contents 1 Gallon



LEWIS COUNTY CHEMICAL
JANITORIAL AND PAPER PRODUCTS



Safe Strip
NO RINSE
WAX STRIPPER